



Features include:

- Cummins 4 Cyl. Engine
- Responsive Hydrostatic Drive
- Articulated Frame for True-tracking Compaction
- ROPS with Sunroof
- Suspension Operator's Seat
- Ballastable from 6.5 to 15 tons
- 100-gallon Pressurized Water Spray System
- All-wheel Oscillation
- Coco Mats with Spring-loaded Scrapers
- 11-Wheel Option

Specifications

DIMENSIONS

Weight	13,500 lbs (6,124 kg)
Fully Ballasted Weight	30,500 lbs (13,835 kg)
Length	14'4" (4.37 m)
Body Width	72" (1.83 m)
Rolling Width	68" (1.73 m)
Height with ROPS	9'5" (2.87 m)
Height without ROPS	85" (2.16 m)
Wheelbase	100" (2.54 m)
Ground Clearance	11" (279 mm)
Inside Turning Radius	110" (2.79 m)

FRAME

Plate steel, welded throughout

ENGINE

85 HP @ 2,600 RPM (63 kw) Cummins

TRANSMISSION

Hydrostatic (no chain drive)

RUBBER TIRES

Number of Tires	9
Size	7:50 x 15 (14-ply) smooth
Tire Overlap	1/2 inch (12.7 mm)

SPEED

0-15 mph (0-24 kph)

ARTICULATION/OSCILLATION

Frame Articulation	+/- 39°
Frame Oscillation	+/- 10°
Tire Oscillation	+/- 4°

PRESSURIZED WATER SYSTEM

Capacity	100 gallons (379 l)
----------	---------------------

FLUID CAPACITIES

Hydraulic Reservoir	14 gallons (53 l)
Fuel	35 gallons (133 l)